



Fiberglass Reinforcement wrapped inside and outside

Polymer Concrete Box and cover  
 Available with 1 or 2 Piece cover  
 Non Skid Surface on Cover  
 Logo Options: Drop in / Embossed  
 Hex Bolts (2)  
 Lift Pins (2) Places  
 Tier 15 or 22  
 Available depths: 18", 24", 30", 36", 48"

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DURABLE ENCLOSURES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF DURABLE ENCLOSURES IS PROHIBITED.

|             |         |  |           |      |              |         |
|-------------|---------|--|-----------|------|--------------|---------|
| Pallet Qty  | 18"-4   | UNLESS OTHERWISE SPECIFIED:<br>DIMENSIONS ARE IN INCHES<br>TOLERANCES:<br>FRACTIONAL<br>ANGULAR: MACH BEND<br>TWO PLACE DECIMAL<br>THREE PLACE DECIMAL | NAME      | DATE |              |         |
|             | 24"-3   |  | DRAWN     | MC   |              | 1/15/24 |
|             | 30"-2   |  | CHECKED   |      |              |         |
|             | 36"-2   |  | ENG APPR. |      |              |         |
|             | 48"-1   |  | MFG APPR. |      |              |         |
| NEXT ASSY   | USED ON | INTERPRET GEOMETRIC TOLERANCING PER:   | Q.A.      |      | COMMENTS:    |         |
| APPLICATION |         | MATERIAL   |           |      |              |         |
|             |         | FINISH   |           |      | SIZE         |         |
|             |         | DO NOT SCALE DRAWING   |           |      | DWG. NO.     |         |
|             |         |  |           |      | DPC304836    |         |
|             |         |  |           |      | REV          |         |
|             |         |  |           |      | SCALE:       |         |
|             |         |  |           |      | WEIGHT:      |         |
|             |         |  |           |      | SHEET 1 OF 1 |         |